Joinwit OTDR Launch Cable Box Length

Description

OTDR Launch Cable Box is designed to aid in the testing of fiber optic cable when using an OTDR. OTDR Launch Cable Box is used with Optical Time Domain Reflectometers (OTDRs) to help minimize the effects of the OTDRs launch pulse on measurement uncertainty. Available in many different configurations and fiber lengths.

Features

* Calibration Compound Latch for positive seal
* Easy opening with locking feature
* Non metal construction will not dent, corrode, or conduce electricity
* Water and dust prove allowing the unit to be taken into almost any environment
* Case can house up to 2,000 meters of fiber Auto Purge Valve for changes in altitude and temperature in altitude and temperature

Specification

Product name	OTDR Launch Cable Box
Dimensions	24cm*14cm*6.6cm
Material	SR Polypropylene
Weight	0.75kg
Operating temperature	-40° to +55°C
Typical Loss	< 0.5dB @ 1310nM for 1000 meters

Order information

JW-LB-SM05	OTDR Launch Cable Box, SM G652D, 500M, Connector: FC/UPC, SC/UPC, ST/UPC, SC/APC, FC/APC, LC/UPC, LC/APC optional
JW-LB-SM10	OTDR Launch Cable Box, SM G652D, 1KM, Connector: FC/UPC, SC/UPC, ST/UPC, SC/APC, FC/APC, LC/UPC, LC/APC optional
JW-LB-SM20	OTDR Launch Cable Box, SM G652D, 2KM, Connector: FC/UPC, SC/UPC, ST/UPC, SC/APC, FC/APC, LC/UPC, LC/APC optional
JW-LB-MM05	OTDR Launch Cable Box, MM (62.5/125um or 50/125um), 500M,Connector: FC/PC, SC/PC, ST/PC, LC/PC optional
JW-LB-MM10	OTDR Launch Cable Box, MM (62.5/125um or 50/125um), 1KM,Connector: FC/PC, SC/PC, ST/PC, LC/PC optional
JW-LB-MM20	OTDR Launch Cable Box, MM (62.5/125um or 50/125um), 2KM,Connector: FC/PC, SC/PC, ST/PC, LC/PC optional